

ATS – Räder-Verwendungsbereiche 2009 / ATS – Wheel Applications 2009

Fahrzeugtyp	Marke	Abbildung	Radgröße	ET	Artikel-Nr.	VS-Set	Rad- kappe	Leistung (kW)	empfohlene Reifengrößen	Freigabe
Car type	Brand	Picture	Wheelsize	Off- set	Reference-No.	VS-Set	Cap	H-power (kW)	Recommended tire sizes	Release
Rover / MG										
			Lochkreis/pcd: 100/4			Nabenbohrung/centre bore:			56,1	
Rover 2..., 25, MG ZR Typ RF, F	Exclusive	V	5,5Jx14H2	35	V 554.EX.35	1341	EC-26	55-107	175/65, 185/60	ABE
	Exclusive	V		43	V 554.EX.43	1341	EC-26	55-107	175/65, 185/60	ABE
	Exclusive	W		35	W 554.EX.35	1341	EC-11	55-107	175/65, 185/60	ABE
	Exclusive	W		43	W 554.EX.43	1341	EC-11	55-107	175/65, 185/60	ABE
	Exclusive	V	6,5Jx15H2	38	V 655.EX.38	1341	EC-26	55-107	185/55, 195/50	TÜV
	Exclusive	W		38	W 655.EX.38	1341	EC-26	55-107	185/55, 195/50	TÜV
	Exclusive	Z		35	Z 655.EX.35	1341	EC-26	55-107	185/55, 195/50	TÜV
	ATS	DTC	7Jx15H2	35	70555.35.52	1341	EC-30	55-107	185/55, 195/50	TÜV
	Exclusive	O		38	O 705.EX.38	1341	EC-26	55-107	185/55, 195/50	TÜV
	Exclusive	W	6,5Jx16H2	42	W 656.EX.42	1341	EC-26	55-107	195/50, 205/45	TÜV
	ATS	Taurus	7Jx16H2	38	70615.38.04	1341	EC-11	55-107	205/45, 215/40	TÜV
	Exclusive	V		37	V 706.EX.37	1341	EC-26	55-107	205/45, 215/40	TÜV
	Exclusive	Z		37	Z 706.EX.37	1341	EC-26	55-107	205/45, 215/40	TÜV
	ATS	Pegasus	7,5Jx16H2	37	75615.37.04	1341	EC-11	55-107	205/45, 215/40	TÜV
	Exclusive	O		37	O 756.EX.37	1341	EC-26	55-107	205/45, 215/40	TÜV
	ATS	DTM-Fix	7,5Jx17H2	38	75713.38.04	1341	2009	55-107	205/40, 215/35	TÜV
ATS	Pegasus		37	75715.37.04	1341	EC-11	55-107	205/40, 215/35	TÜV	
Exclusive	O		38	O 757.EX.38	1341	EC-26	55-107	205/40, 215/35	TÜV	
			Lochkreis/pcd: 100/4			Nabenbohrung/centre bore:			56,1	
Rover 4..., 45, MG ZS Typ RT, T	Exclusive	V	5,5Jx14H2	35	V 554.EX.35	1341	EC-26	55-100	175/65, 185/60	ABE
	Exclusive	V		43	V 554.EX.43	1341	EC-26	55-100	175/65, 185/60	ABE
	Exclusive	W		35	W 554.EX.35	1341	EC-11	55-100	175/65, 185/60	ABE
	Exclusive	W		43	W 554.EX.43	1341	EC-11	55-100	175/65, 185/60	ABE
	Exclusive	V	6,5Jx15H2	38	V 655.EX.38	1341	EC-26	55-110	185/55, 195/50	ABE/TÜV
	Exclusive	W		38	W 655.EX.38	1341	EC-26	55-110	185/55, 195/50	ABE/TÜV
	Exclusive	Z		35	Z 655.EX.35	1341	EC-26	55-110	185/55, 195/50	ABE/TÜV
	ATS	DTC	7Jx15H2	35	70555.35.52	1341	EC-30	55-110	185/55, 195/50	TÜV
	Exclusive	O		38	O 705.EX.38	1341	EC-26	55-110	185/55, 195/50	ABE/TÜV
	Exclusive	W	6,5Jx16H2	42	W 656.EX.42	1341	EC-26	55-110	195/45, 205/45	ABE/TÜV
	ATS	Taurus	7Jx16H2	38	70615.38.04	1341	EC-11	55-110	205/45, 215/40	TÜV
	Exclusive	V		37	V 706.EX.37	1341	EC-26	55-110	205/45, 215/40	TÜV
	Exclusive	Z		37	Z 706.EX.37	1341	EC-26	55-110	205/45, 215/40	TÜV
	ATS	Pegasus	7,5Jx16H2	37	75615.37.04	1341	EC-11	55-110	205/45, 215/40	TÜV
	Exclusive	O		37	O 756.EX.37	1341	EC-26	55-110	205/45, 215/40	TÜV
	ATS	DTM-Fix	7,5Jx17H2	38	75713.38.04	1341	2009	55-110	205/40	TÜV
ATS	Pegasus		37	75715.37.04	1341	EC-11	55-110	205/40	TÜV	
Exclusive	O		38	O 757.EX.38	1341	EC-26	55-110	205/40	TÜV	
			Lochkreis/pcd: 114,3/4			Nabenbohrung/centre bore:			64,1	
Rover 6.. Typ RH	Exclusive	W	6,5Jx15H2	38	W 655.LY.38	2141	EC-26	77-116	185/65, 195/60	ABE/TÜV
	ATS	DTM-Fix	7,5Jx17H2	38	75713.38.11	2141	2009	77-147	205/45, 215/45	TÜV
			Lochkreis/pcd: 100/5			Nabenbohrung/centre bore:			56,1	
Rover 75 inkl. Tourer MG ZT, ZT-T Typ RJ	Exclusive	V	6,5Jx15H2	38	V 655.FX.38	1350	EC-26	85-130	195/65, 205/65	ABE/TÜV
	Exclusive	W		38	W 655.FX.38	1350	EC-26	85-130	195/65, 205/65	ABE/TÜV
	Exclusive	Z		35	Z 655.FX.35	1350	EC-26	85-130	195/65, 205/65	ABE/TÜV
	Exclusive	O	7Jx15H2	38	O 705.FX.38	1350	EC-26	85-130	195/65, 205/65	ABE/TÜV
	Exclusive	W	6,5Jx16H2	38	W 656.FX.38	1350	EC-26	85-130	205/55, 215/55	TÜV
	ATS	Sirius	7Jx16H2	35	70614.35.05	1350	2009	85-130	205/55, 215/55	TÜV
	ATS	Taurus		38	70615.38.05	1350	EC-11	85-130	205/55, 215/55	TÜV
	Exclusive	V		37	V 706.FX.37	1350	EC-26	85-130	205/55, 215/55	TÜV
	Exclusive	Z		37	Z 706.FX.37	1350	EC-26	85-130	205/55, 215/55	TÜV
	ATS	Pegasus	7,5Jx16H2	37	75615.37.05	1350	EC-11	85-130	205/55, 215/55	TÜV
	Exclusive	O		37	O 756.FX.37	1350	EC-26	85-130	205/55, 215/55	TÜV
	ATS	Sirius	7Jx17H2	37	70715.37.05	1350	2009	85-130	205/50, 225/45	TÜV
	ATS	DTM-Fix	7,5Jx17H2	38	75713.38.05	1350	2009	85-130	205/50, 225/45	TÜV
	ATS	DTC		35	75714.35.55	4441	EC-30	85-130	205/50, 225/45	TÜV
	ATS	Pegasus		37	75715.37.05	1350	EC-11	85-130	205/50, 225/45	TÜV
	Exclusive	O		38	O 757.FX.38	1350	EC-26	85-130	205/50, 225/45	TÜV
	Exclusive	V		37	V 757.FX.37	1350	EC-26	85-130	205/50, 225/45	TÜV
	Exclusive	Z		37	Z 757.FX.37	1350	EC-26	85-130	205/50, 225/45	TÜV
	ATS	Apollo 11	8Jx17H2	35	80717.35.05	1350	EC-11	85-130	205/50, 225/45	TÜV
	ATS	Taurus		35	80718.35.05	1350	EC-11	85-130	205/50, 225/45	TÜV
	Exclusive	O		35	O 807.FX.35	1350	EC-26	85-130	205/50, 225/45	TÜV
	ATS	Sirius	7,5Jx18H2	37	75810.37.05	1350	2009	85-130	225/40	TÜV
	ATS	DTM	8Jx18H2	35	80816.35.05.C	002	2011	85-130	225/40	TÜV
	ATS	DTM-Fix		35	80817.35.05	1350	2009	85-130	225/40	TÜV
	ATS	Pegasus		35	80820.35.05	1350	EC-11	85-130	225/40	TÜV
	Exclusive	Z		35	Z 808.FX.35	1350	EC-26	85-130	225/40	TÜV
ATS	Sirius	8Jx19H2	35	80913.35.05	1350	2009	85-130	225/35	TÜV	

Achtung! Maßgebend für die Zuordnung der Räder zu den jeweiligen Fahrzeugen sind ausschließlich die ABE bzw. TÜV-Gutachten!